

Reflection LEDko EXT IP65

White 3200 K or 5600 K



KEY FEATURES

- First IP65 protection rating LED profile on the market
- Extreme lumen/W efficiency (150 W led engine)
- Instant gobos from standard printers
- Think aluminum, long lasting light source in long lasting body
- No maintenance required
- Profile Zoom 26°- 40°

SPECIFICATIONS

- Fixed white color temperature 3200 K or 5600 K
- Profile Zoom from 26° to 40°
- Four blade framing system, each shutter blade is adjustable for radial position and angle
- Electronic 16 bit dimming with 2 selectable curves, simulating halogen or discharge lamp based fixtures
- Synchronized, random or pulse electronic strobe
- Flicker free operation with LEDs frequency controlled via DMX from 600 Hz to 19000 Hz
- Fan setting with 4 different options (low-noise, auto-silent, DMX, maximum speed)
- Weatherproof rating IP 65

PHYSICAL SIZE

- Length: 603 mm (23.7 in)
- Height: 180 mm (7.0 in)
- Height with bracket: 365 mm (14.3 in)
- Width: 212 mm (8.3 in)
- Weight: 14.0 Kg (30.8 lbs)

LIGHT SOURCE

- Modular 150 W COB LED
- LEDs life: 20000 hours at 70% lumen intensity maintenance

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512A
- DMX Channels: 5/1
- Setting, addressing, testing and measurements via LEDs display
- RDM

ELECTRICAL SPECIFICATIONS/ CONNECTIONS

- AC power: 90-250 V, auto sensing, 50/60 Hz
- Integral cable without power plug
- Power consumption: 0.81 A at 230 V, 2.07 A at 90 V - $\cos\phi$ 0.9
- DMX data in/out: 5 pin locking XLR

LEDko EXT W 3200 K
10011A607 Black

LEDko EXT W 5600 K
10011A611 Black