

channel	function	type of control	effect	decimal	percentage
<b>1</b>	master dimmer	proportional	adjust luminous output intensity from 0% to 100%	0 - 255	0% - 100%
<b>2</b>	dimmer fine	proportional	fine dimmer control 16 bit	0 - 255	0% - 100%
<b>3</b>	white tone	step	3200 K	0 - 10	0% - 4%
			2700 K	11 - 16	4% - 6%
			2800 K	17 - 22	7% - 9%
			2900 K	23 - 28	9% - 11%
			3000 K	29 - 34	11% - 13%
			3100 K	35 - 40	14% - 16%
			3200 K	41 - 46	16% - 18%
			3300 K	47 - 52	18% - 20%
			3400 K	53 - 58	21% - 23%
			3500 K	59 - 64	23% - 25%
			3600 K	65 - 70	25% - 27%
			3700 K	71 - 76	28% - 30%
			3800 K	77 - 82	30% - 32%
			3900 K	83 - 88	33% - 35%
			4000 K	89 - 94	35% - 37%
			4100 K	95 - 100	37% - 39%
			4200 K	101 - 106	40% - 42%
			4300 K	107 - 112	42% - 44%
			4400 K	113 - 118	44% - 46%
			4500 K	119 - 124	47% - 49%
			4600 K	125 - 130	49% - 51%
			4700 K	131 - 136	51% - 53%
			4800 K	137 - 142	54% - 53%
			4900 K	143 - 148	56% - 56%
			5000 K	149 - 154	58% - 60%
			5100 K	155 - 160	61% - 63%
			5200 K	161 - 166	63% - 65%
			5300 K	167 - 172	65% - 67%
5400 K	173 - 178	68% - 70%			
5500 K	179 - 184	70% - 72%			
5600 K	185 - 190	73% - 75%			
5700 K	191 - 196	75% - 77%			
5800 K	197 - 202	77% - 79%			
5900 K	203 - 208	80% - 82%			
6000 K	209 - 214	82% - 84%			
6100 K	215 - 220	84% - 86%			
6200 K	221 - 226	87% - 89%			
6300 K	227 - 232	89% - 91%			
6400 K	233 - 238	91% - 93%			
6500 K	239 - 244	94% - 96%			
5600 K	245 - 255	96% - 100%			

<b>4</b>	white fine temperature	step	no effect	0		0%				
		proportional	from the previous step to temperature selected	1	- 126	0%	- 49%			
		step	no effect	127	- 128	50%	- 50%			
		proportional	from temperature selected the following step	129	- 254	51%	- 100%			
		step	no effect	255		100%				
<b>5</b>	strobe effect	step	no effect	0	- 9	0%	- 4%			
		proportional	variable speed strobing effect, from slow to fast	10	- 57	4%	- 22%			
		step	stop strobe	58	- 59	23%	- 23%			
		proportional	sequenced pulsed strobe, slow closing, fast operating (variable speed pulsing, from slow to fast)	60	- 108	24%	- 42%			
		step	stop strobe	109	- 110	43%	- 43%			
		proportional	sequenced pulsed strobe, fast closing, slow operating (variable speed pulsing, from slow to fast)	111	- 159	44%	- 62%			
		step	stop strobe	160	- 161	63%	- 63%			
		proportional	random strobe effect with variable speed from slow to fast and synchronized colors	162	- 207	64%	- 81%			
		step	stop strobe	208	- 209	82%	- 82%			
		proportional	random strobe effect with variable speed from slow to fast and non-synchronized colors	210	- 255	82%	- 100%			
<b>6</b>	special function	step	park	0	- 9	0%	- 4%			
			no effect	10	- 71	4%	- 28%			
			600 Hz	72	- 84	28%	- 33%			
			fan at low-noise speed	85	- 96	33%	- 38%			
			fan at auto speed	97	- 108	38%	- 42%			
		proportional	fan speed control from minimum to maximum	109	- 120	43%	- 47%			
		step	no effect	121	- 133	47%	- 52%			
			enables the automatic display blackout	134	- 185	53%	- 73%			
			disables the automatic display blackout	186	- 199	73%	- 78%			
			LED control frequency tuning 1.000 Hz	200	- 205	78%	- 80%			
			LED control frequency tuning 3.000 Hz	206	- 211	81%	- 83%			
			LED control frequency tuning 6.000 Hz	212	- 217	83%	- 85%			
			LED control frequency tuning 8.000 Hz	218	- 223	85%	- 87%			
			LED control frequency tuning 10.000 Hz	224	- 229	88%	- 90%			
			LED control frequency tuning 12.000 Hz	230	- 235	90%	- 92%			
			LED control frequency tuning 14.000 Hz	236	- 241	93%	- 95%			
			LED control frequency tuning 16.000 Hz	242	- 247	95%	- 97%			
			LED control frequency tuning 19.000 Hz	248	- 255	97%	- 100%			
			<b>Projector:</b> SoftLite Led VariWhite			<b>Chart name:</b> DMX512 function		<b>software version:</b> 1.14 or following		
			<b>Edition:</b> 2			<b>Date:</b> 10.10.2019				

channel	function	type of control	effect	decimal	percentage	
<b>1</b>	<b>1</b>	master dimmer	proportional	adjust luminous output intensity from 0% to 100%	0 - 255 0% - 100%	
			3200 K	0 - 10	0% - 4%	
			2700 K	11 - 16	4% - 6%	
			2800 K	17 - 22	7% - 9%	
			2900 K	23 - 28	9% - 11%	
			3000 K	29 - 34	11% - 13%	
			3100 K	35 - 40	14% - 16%	
			3200 K	41 - 46	16% - 18%	
			3300 K	47 - 52	18% - 20%	
			3400 K	53 - 58	21% - 23%	
			3500 K	59 - 64	23% - 25%	
			3600 K	65 - 70	25% - 27%	
			3700 K	71 - 76	28% - 30%	
			3800 K	77 - 82	30% - 32%	
			3900 K	83 - 88	33% - 35%	
			4000 K	89 - 94	35% - 37%	
			4100 K	95 - 100	37% - 39%	
			4200 K	101 - 106	40% - 42%	
			4300 K	107 - 112	42% - 44%	
			4400 K	113 - 118	44% - 46%	
			4500 K	119 - 124	47% - 49%	
<b>2</b>	<b>-</b>	white tone	step	4600 K	125 - 130	49% - 51%
				4700 K	131 - 136	51% - 53%
				4800 K	137 - 142	54% - 53%
				4900 K	143 - 148	56% - 56%
				5000 K	149 - 154	58% - 60%
				5100 K	155 - 160	61% - 63%
				5200 K	161 - 166	63% - 65%
				5300 K	167 - 172	65% - 67%
				5400 K	173 - 178	68% - 70%
				5500 K	179 - 184	70% - 72%
				5600 K	185 - 190	73% - 75%
				5700 K	191 - 196	75% - 77%
				5800 K	197 - 202	77% - 79%
				5900 K	203 - 208	80% - 82%
				6000 K	209 - 214	82% - 84%
				6100 K	215 - 220	84% - 86%
				6200 K	221 - 226	87% - 89%
				6300 K	227 - 232	89% - 91%
				6400 K	233 - 238	91% - 93%
				6500 K	239 - 244	94% - 96%
				5600 K	245 - 255	96% - 100%
<b>Projector:</b> SoftLite Led VariWhite			<b>Chart name:</b> DMX512 function	<b>software version:</b> 1.14 or following		
<b>Edition:</b> 2			<b>Date:</b> 10.10.2019			