



RegoLed 5CH DMX512

Product code: AC10005E011

KEY FEATURES

- PWM frequency adjustment from 500 to 30.000 Hz
- Max output current: 5 x 8 A
- Max output power: 96 W at 12 V or 192 W at 24 V for each channel



SPECIFICATIONS

- DC voltage Power Supply
- Directly controlled with DMX signal
- PWM frequency adjustment: from 500 to 30.000 Hz
- 31 internal programs
- 5 different electrical channels, individually controlled
- Electronic dimmer (9 selectable curves)
- Electronic strobe
- IP rating: 20

PHYSICAL SIZE

- Length: 164 mm (6.45 in)
- Width: 73 mm (2.87 in)
- Height: 38 mm (1.49 in)
- Weight: 0.5 Kg (1.1 lbs)

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512A
- DMX channels: 7 / 5
- Setting and addressing by display
- RDM (Remote Device Management)

ELECTRICAL SPECIFICATIONS AND CONNECTIONS

- DC Power: 12 V - 24 V
- Max output current: 5 x 8 A
- Max output power: 5 x (96 - 192) W
- DMX In/Out ports: RJ45, 5 pin locking XLR

DRAWING SIZE

