



**SEZIONE CAVI/wire section:**

- 1= 5 mm<sup>2</sup>
- 2= 5 mm<sup>2</sup>
- 3= 2.5 mm<sup>2</sup>
- 4= 2.5 mm<sup>2</sup>
- 5= 2.5 mm<sup>2</sup>
- 51= 2.5 mm<sup>2</sup>
- 52= 2.5 mm<sup>2</sup>
- 53= 2.5 mm<sup>2</sup>
- 54= 4 mm<sup>2</sup>
- 6= 5 mm<sup>2</sup>
- 11= 2.5 mm<sup>2</sup>
- 12= 2.5 mm<sup>2</sup>
- B= 4 mm<sup>2</sup>

**CARATTERISTICHE ELETTRICHE**  
**ELECTRICAL CHARACTERISTICS**

Lamp Current      I<sub>l</sub> = 26 A  
 Lamp Voltage      V<sub>l</sub> = 123 V  
 Starting Voltage    V<sub>s</sub> = 9 KV

9	12.06.14
8	30.06.97
7	5.11.96
6	15.12.93
5	08.04.93
4	23.12.91
3	17.07.91
2	29.01.91
1	21.09.90



No.	Data
MODIFICHE	



CASTEL GOFFREDO (MN) ITALIA  
 VIA INGILTERRA ZONA IND. EST

tel: (0376) 779336 telex: 301590 fax: (0376) 780657

DISEGNATORE:

DATA: 30.07.90

**SCHEMA ELETTRICO**  
**TESTA 2500 W HTI/SE con**  
**Stand by.**  
**WIRING DIAGRAM FOR TESTA**  
**2500 W HTI/SE with stand by.**

SCHEMA No: 113

SOTTOSHEMA No: 8