

iSpot eXtreme 6000

SPECIFICATIONS

- CMY color mixing
- 5 colors + open
- 5 CTO filters
- Proportional frost
- 1 aerial wheel, 6 rotating gobos + open
- 1 break-up wheel, 6 rotating gobos + open
- 2 rotating prisms (with 3D effect)
- Focus
- Proportional zoom 7°- 26°
- Iris
- Dimmer
- Mechanical strobe, electronic strobe (zap effect), synchronized, random, pulse effect
- Pan 530°, Tilt 270°, 16 bit

PHYSICAL SIZE

- Length: 485 mm (19.1 in)
- Width: 505 mm (19.9 in)
- Height: 780 mm (30.7 in), head straight up
- Weight: 38 kg (83.8 lbs)

LAMP AND BALLAST

- Type: Philips MSR Gold 1200SA/SE
- Color temperature: 6300 Kelvin
- Color rendering index: 80
- Average lamp life: 500 hours
- Socket: PG950
- Electronic ballast with Power Factor Correction

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990
- DMX channels: 24
- Setting and addressing: led display or remotely

ELECTRICAL SPECIFICATIONS/CONNECTIONS

- AC power: 200-208/230/240 V, 50/60 Hz, 2m (6.6 ft) integral cable without power plug
- Power consumption: 8 A at 230 V
- DMX data in/out: 3 pin and 5 pin locking XLR
- RJ45 for upload and remote control



iSpot eXtreme 6000 - # 9133