

Riga Led

SPECIFICATIONS

- RGB color mixing
- Beam angle: 74° (RigaLed A), 96° (RigaLed S)
- IP 20 weatherproof rating

PHYSICAL SIZE

- Length RigaLed 50: 514 mm (20.2 in)
- Length RigaLed 100: 1019 mm (40.1 in)
- Width: 40 mm (1.6 in)
- Height: 72 mm (2.8 in)
- Weight RigaLed 50: 0.7 kg (1.5 lbs)
- Weight RigaLed 100: 1.4 kg (3.1 lbs)

LIGHT SOURCE

- 150 Leds (RigaLed 50) or 300 (RigaLed 100)

CONTROL PROTOCOL AND PROGRAMMING

- With RegoLed

ELECTRICAL SPECIFICATIONS/CONNECTIONS

- DC power: 24 V, 0.2m (0.6 ft) integral cable with quick connector IN/OUT
- Power consumption RigaLed 50: 0.8 A at 24 V
- Power consumption RigaLed 100: 1.6 A at 24 V

ACCESSORIES

- Connection cable 0.5 m (# CV11)
- Connection cable 1 m (# CV12)
- Connection cable 5 m (# CV13)
- Diamond Light-Shape (RigaLed 1m) - # KIT143
- Diamond Light-Shape (RigaLed 0,5m) - # KIT143/1

