

channel	function	type of control	effect	decimal		percentage	
1	master dimmer	proportional	adjust luminous output intensity from 0% to 100%	0	- 255	0%	- 100%
2	dimmer fine	proportional	fine dimmer control 16 bit	0	- 255	0%	- 100%
3	white tone	step	3.200 K	0	- 10	0%	- 4%
			2.700 K	11	- 16	4%	- 6%
			2.800 K	17	- 22	7%	- 9%
			2.900 K	23	- 28	9%	- 11%
			3.000 K	29	- 34	11%	- 13%
			3.100 K	35	- 40	14%	- 16%
			3.200 K	41	- 46	16%	- 18%
			3.300 K	47	- 52	18%	- 20%
			3.400 K	53	- 58	21%	- 23%
			3.500 K	59	- 64	23%	- 25%
			3.600 K	65	- 70	25%	- 27%
			3.700 K	71	- 76	28%	- 30%
			3.800 K	77	- 82	30%	- 32%
			3.900 K	83	- 88	33%	- 35%
			4.000 K	89	- 94	35%	- 37%
			4.100 K	95	- 100	37%	- 39%
			4.200 K	101	- 106	40%	- 42%
			4.300 K	107	- 112	42%	- 44%
			4.400 K	113	- 118	44%	- 46%
			4.500 K	119	- 124	47%	- 49%
			4.600 K	125	- 130	49%	- 51%
			4.700 K	131	- 136	51%	- 53%
			4.800 K	137	- 142	54%	- 53%
			4.900 K	143	- 148	56%	- 56%
			5.000 K	149	- 154	58%	- 60%
			5.100 K	155	- 160	61%	- 63%
			5.200 K	161	- 166	63%	- 65%
5.300 K	167	- 172	65%	- 67%			
5.400 K	173	- 178	68%	- 70%			
5.500 K	179	- 184	70%	- 72%			
5.600 K	185	- 190	73%	- 75%			
5.700 K	191	- 196	75%	- 77%			
5.800 K	197	- 202	77%	- 79%			
5.900 K	203	- 208	80%	- 82%			
6.000 K	209	- 214	82%	- 84%			
6.100 K	215	- 220	84%	- 86%			
6.200 K	221	- 226	87%	- 89%			
6.300 K	227	- 232	89%	- 91%			
6.400 K	233	- 238	91%	- 93%			
6.500 K	239	- 244	94%	- 96%			
5.600 K	245	- 255	96%	- 100%			

4	fine white tone	step	no effect	0		0%	
		proportional	from the previous step to temperature selected	1	- 126	1%	- 49%
		step	no effect	127	- 128	50%	- 50%
		proportional	from temperature selected the following step	129	- 254	51%	- 99%
		step	no effect	255		100%	
5	strobe effect	step	no effect	0	- 9	0%	- 4%
		proportional	variable speed strobing effect, from slow to fast	10	- 57	4%	- 22%
		step	stop strobe	58	- 59	23%	- 23%
		proportional	sequenced pulsed strobe, slow closing, fast operating (variable speed pulsing, from slow to fast)	60	- 108	24%	- 42%
		step	stop strobe	109	- 110	43%	- 43%
		proportional	sequenced pulsed strobe, fast closing, slow operating (variable speed pulsing, from slow to fast)	111	- 159	44%	- 62%
		step	stop strobe	160	- 161	63%	- 63%
		proportional	random strobe effect with variable speed from slow to fast and synchronized colors	162	- 207	64%	- 81%
		step	stop strobe	208	- 209	82%	- 82%
		proportional	random strobe effect with variable speed from slow to fast and non-synchronized colors	210	- 255	82%	- 100%
6	special function	step	no effect	0	- 9	0%	- 4%
			600 Hz	10	- 84	4%	- 33%
			fan at low-noise speed	85	- 96	33%	- 38%
			fan at auto speed	97	- 108	38%	- 42%
		proportional	fan speed control	109	- 120	43%	- 47%
		step	no effect	121	- 133	47%	- 52%
			enables the automatic display blackout	134	- 185	53%	- 73%
			disables the automatic display blackout	186	- 199	73%	- 78%
			LED control frequency tuning 1.000 Hz	200	- 205	78%	- 80%
			LED control frequency tuning 3.000 Hz	206	- 211	81%	- 83%
			LED control frequency tuning 6.000 Hz	212	- 217	83%	- 85%
			LED control frequency tuning 8.000 Hz	218	- 223	85%	- 87%
			LED control frequency tuning 10.000 Hz	224	- 229	88%	- 90%
			LED control frequency tuning 12.000 Hz	230	- 235	90%	- 92%
			LED control frequency tuning 14.000 Hz	236	- 241	93%	- 95%
			LED control frequency tuning 16.000 Hz	242	- 247	95%	- 97%
			LED control frequency tuning 19.000 Hz	248	- 255	97%	- 100%

Note: the one channel function mode can be selected through the DMX function menu. The color of the light will be the last selected when changing mode

Projector: LEDko VariWhite 2

Chart name: DMX512 function

software version: 1.11 or following

Edition: 6

Date: 15.11.2019

channel		function	type of control	effect	decimal		percentage	
2	1							
1	1	master dimmer	proportional	adjust luminous output intensity from 0% to 100%	0	- 255	0%	- 100%
2	-	white tone	step	3.200 K	0	- 10	0%	- 4%
				2.700 K	11	- 16	4%	- 6%
				2.800 K	17	- 22	7%	- 9%
				2.900 K	23	- 28	9%	- 11%
				3.000 K	29	- 34	11%	- 13%
				3.100 K	35	- 40	14%	- 16%
				3.200 K	41	- 46	16%	- 18%
				3.300 K	47	- 52	18%	- 20%
				3.400 K	53	- 58	21%	- 23%
				3.500 K	59	- 64	23%	- 25%
				3.600 K	65	- 70	25%	- 27%
				3.700 K	71	- 76	28%	- 30%
				3.800 K	77	- 82	30%	- 32%
				3.900 K	83	- 88	33%	- 35%
				4.000 K	89	- 94	35%	- 37%
				4.100 K	95	- 100	37%	- 39%
				4.200 K	101	- 106	40%	- 42%
				4.300 K	107	- 112	42%	- 44%
				4.400 K	113	- 118	44%	- 46%
				4.500 K	119	- 124	47%	- 49%
				4.600 K	125	- 130	49%	- 51%
				4.700 K	131	- 136	51%	- 53%
				4.800 K	137	- 142	54%	- 53%
				4.900 K	143	- 148	56%	- 56%
				5.000 K	149	- 154	58%	- 60%
5.100 K	155	- 160	61%	- 63%				
5.200 K	161	- 166	63%	- 65%				
5.300 K	167	- 172	65%	- 67%				
5.400 K	173	- 178	68%	- 70%				
5.500 K	179	- 184	70%	- 72%				
5.600 K	185	- 190	73%	- 75%				
5.700 K	191	- 196	75%	- 77%				
5.800 K	197	- 202	77%	- 79%				
5.900 K	203	- 208	80%	- 82%				
6.000 K	209	- 214	82%	- 84%				
6.100 K	215	- 220	84%	- 86%				
6.200 K	221	- 226	87%	- 89%				
6.300 K	227	- 232	89%	- 91%				
6.400 K	233	- 238	91%	- 93%				
6.500 K	239	- 244	94%	- 96%				
5.600 K	245	- 255	96%	- 100%				
Projector: LEDko VariWhite 2				Chart name: DMX512 function		software version: 1.11 or following		
Edition: 6				Date: 15.11.2019				