zones	channel	function	type of control	effect	decimal		nal	percentage		
	1	master dimmer	proportional	adjust luminous output intensity from 0 to 100%	0	-	255	0%	- 100%	
Line 1	2	red	proportional	proportional control of the percentage of red colour from 0 to 100%	0	-	255	0%	- 1009	
	3	green	proportional	proportional control of the percentage of green colour from 0 to 100%	0	-	255	0%	- 100%	
	4	blue	proportional	proportional control of the percentage of blue colour from 0 to 100%	0	-	255	0%	- 1009	
	5	white	proportional	proportional control of the percentage of white light from 0 to 100%	0	-	255	0%	- 1009	
Line 2	6	red	proportional	proportional control of the percentage of red colour from 0 to 100%	0	-	255	0%	- 100%	
	7	green	proportional	proportional control of the percentage of green colour from 0 to 100%	0	-	255	0%	- 1009	
	8	blue	proportional	proportional control of the percentage of blue colour from 0 to 100%	0	-	255	0%	- 100%	
	9	white	proportional	proportional control of the percentage of white light from 0 to 100%	0	-	255	0%	- 100%	
Line 3	10	red	proportional	proportional control of the percentage of red colour from 0 to 100%	0	-	255	0%	- 1009	
	11	green	proportional	proportional control of the percentage of green colour from 0 to 100%	0	-	255	0%	- 100%	
Ė	12	blue	proportional	proportional control of the percentage of blue colour from 0 to 100%	0	-	255	0%	- 100%	
	13	white	proportional	proportional control of the percentage of white light from 0 to 100%	0	-	255	0%	- 1009	
	14	strobe effect	step proportional step	no effect variable speed strobing effect, from slow to fast stop strobe sequenced pulse effect, slow closing, fast opening	0 10 58	-	9 57 59	0% 4% 23%	- 4% - 22% - 23%	
			proportional step	(variable speed pulsing, from slow to fast) stop strobe	109	-	108	24% 43%	- 42% - 43%	
			proportional	sequenced pulse effect, fast closing, slow opening (variable speed pulsing, from slow to fast)	111	-	159	44%	- 62%	
			step proportional step	stop strobe random strobe effect with variable speed from slow to fast and synchronised colours stop strobe	160 162 208	Ш	161 207 209	63% 64% 82%	- 63% - 81% - 82%	
			proportional	random strobe effect with variable speed from slow to fast and non-synchronised colours	210	-	255	82%	- 1009	
	15	led line 1	proportional	proportional movement of lower led line in 180°	0	-	255	0%	- 1009	
	16	led line 2	proportional	proportional movement of central led line in 180°	0	-	255	0%	- 100%	
	17	led line 3	proportional	proportional movement of upper led line in 180°	0	-	255	0%	- 1009	
	18		d d proportional a (f)	no effect automated colors program 1; fade speed between colours from fast to slow (from 0,05 second to 1 minute)	0	-	9	0% 4%	- 4% - 16%	
		automated functions and fade speed		automated colors program 2; fade speed between colours from fast to slow (from 0,05 second to 1 minute)	41	-	71	16%	- 28%	
				automated colors program 3; fade speed between colours from fast to slow (from 0,05 second to 1 minute)  automated colors program 4; fade speed between colours from fast to slow	72	-	102	28%	- 40%	
				(from 0,05 second to 1 minute, colors selected from ch. 2 to ch. 13)  automated colors program 5; fade speed between colours from fast to slow (from 0,05 second to 1 minute, colors selected from ch. 2 to ch. 13)	103	-  -	133	40% 53%	- 52% - 64%	
				automated colors program 6; fade speed between colours from fast to slow (from 0,05 second to 1 minute, colors selected from ch. 2 to ch. 13)	165	-	195	65%	- 76%	
				automated colors program 7; fade speed between colours from fast to slow (from 0,05 second to 1 minute, colors selected from ch. 2 to ch. 13)	196	-	225	77%	- 88%	
				automated colors program 8; fade speed between colours from fast to slow (from 0,05 second to 1 minute, colors selected from ch. 2 to ch. 13)	226	-	255	89%	- 100%	

zones	channel	function	type of control	effect		decimal			percentage		
		effects movement	step	no effect	0	-	9	0%	- 4%		
				position 1	10	-	19	4%	- 7%		
				position 2	20	-	39	8%	- 15%		
				position 3	40	-	59	16%	- 23%		
	19			position 4	60	-	79	24%	- 31%		
				position 5	80	-	99	31%	- 39%		
				position 6	100	-	119	39%	- 47%		
			proportional	automated movement program 1 with proportional control over increasing speed	120	-	146	47%	- 57%		
				automated movement program 2 with proportional control over increasing speed	147	-	173	58%	- 68%		
				automated movement program 3 with proportional control over increasing speed	174	-	200	68%	- 78%		
				automated movement program 4 with proportional control over increasing speed	201	-	227	79%	- 89%		
				automated movement program 5 with proportional control over increasing speed	228	-	255	89%	- 100%		
	20	motors reset and special functions	step	no effect	0	-	9	0%	- 4%		
			proportional	control of the pause time between colours (steps) of the program selected from channel 18; the pause time is adjustable proportionally from 1 second to 3.30 minutes	10	-	135	4%	- 53%		
			step	motors reset	136	-	170	53%	- 67%		
				park, no functions	171	-	179	67%	- 70%		
				led control frequency tuning 1000 Hz	180	-	188	71%	- 74%		
				led control frequency tuning 1500 Hz	189	-	197	74%	- 77%		
				led control frequency tuning 2000 Hz	198	-	206	78%	- 81%		
				led control frequency tuning 2500 Hz	207	-	215	81%	- 84%		
				led control frequency tuning 3000 Hz	216	-	224	85%	- 88%		
				led control frequency tuning 3500 Hz	225	-	233	88%	- 91%		
				led control frequency tuning 4000 Hz	234	-	242	92%	- 95%		
				led control frequency tuning 4500 Hz	243	[-]	251	95%	- 98%		
				led control frequency tuning 5000 Hz	252	-	255	99%	- 100%		
Projector: StageLite Led (Line)				Table name: DMX 512 functions							
Table number: 290 Edition: 1			Edition: 1	Date: 20/02/2009							