



## **KEY FEATURES**

- RGBW color mixing
- IP rating: 65 (weatherproof)
- Fast magnetic and mechanical connection system to achieve any kind of composition
- Automatic addressing
- No maintenance required



#### **SPECIFICATIONS**

- RGBW color mixing
- IP rating: 65 (weatherproof)
- Flicker-free operation
- Beam angle: 35°
- 3 different kind of yokes available for mechanical fixing and any orientation

#### LIGHT SOURCE

- 4 LEDs RGBW, 3W each
- Average LED lifetime: a minimum of 80% of the initial luminous flux will be maintained after approx. 50.000 hours of usage (50.000 LM80)

# PHYSICAL SIZE - Length: 89 mm (3.50 in)

- Width: 78 mm (3.07 in)
- Height: 79 mm (3.11 in) - Weight: 1 Kg (2.20 lbs)

#### CONTROL PROTOCOL AND PROGRAMMING

- Through RegoPixel (max 32 Pixel for 1 RegoPixel)
- DMX channels: 4
- RDM (Remote Device Management)

## **ELECTRICAL SPECIFICATIONS** AND CONNECTIONS


- AC power: 48 Vdc
- Internal cable (T connection In/Out)
- Max power consumption: 10 W
- Power consumption: 0.25 A at 48 V cosφ 0,9


#### **ACCESSORIES**


- Short yoke
- Long yoke
- Spherical joint



## DRAWING SIZE







## DMX CHARTS

| 4 channels |       |  |
|------------|-------|--|
| 1          | red   |  |
| 2          | green |  |
| 3          | blue  |  |
| 4          | white |  |

## **ACCESSORIES**

| Code        | Description     |
|-------------|-----------------|
| BC10031A003 | Short yoke      |
| BC10031A004 | Long yoke       |
| BC10031A005 | Spherical joint |