



Gobos size		
	Metal Gobos	Glass Gobos defined
Working area Ø mm. Diametro utile mm.	Up to 25 Fino a 25	Up to 25 Fino a 25
Thickness mm. Spessore mm.	0.5 0.5	From 1 to 4 Da 1 a 4

CODE / CODICE	POS.	DESCRIPTION	N°PCS
GO196	1	Two holes	1
GO246	2	Growing squares	1
GO247	3	Smart blade	1
GO248	4	Loose chips	1
GO198	5	Half moon	1
GO249	6	Tight beam	1



SPARE PARTS DIAGRAM | SCHEMA PARTI DI RICAMBIO

CASTEL GOFFREDO (MN) ITALIA
VIA INGILTERRA ZONA IND. EST
tel: (0376) 77521
fax: (0376) 780657 - 780888 - 780844
www.coemar.com

Duplication of this drawing, either full or in part, is strictly prohibited without prior written authorization from coemar
Questo disegno non può essere copiato, riprodotto, mostrato a terzi
Senza nostra autorizzazione

Date:
Data: 1/03/2012

Revision N.
Versione N°

Revision date:
Data di modifica:

Gobo wheel 2 Vers.2

Fixture.
Proiettore **Infinity Spot XL**

this document refers to fixtures with serial number

Page
Pagina 01 of /di 01

Position ref.
Posizione di rif.