

channel	function	type of control	effect	decimal		percentage	
1	master dimmer	proportional	adjust luminous output intensity from 0 to 100%	0	- 255	0%	- 100%
2	fine white adjust +%	step	no effect	0	- 9	0%	- 4%
		proportional	adjust fine color temperature from 4000°K to 6500°K	10	- 255	4%	- 100%
3	fine white adjust -%	step	no effect	0	- 9	0%	- 4%
		proportional	adjust fine color temperature from 4000°K to 2700°K	10	- 255	4%	- 100%
Note 1: channel 2 and 3 have full effect when one of them have zero value. Note 2: measurements were performed with 12° optics.							
4	strobe	step	no effect	0	- 9	0%	- 4%
		proportional	variable speed strobing effect, from slow to fast	10	- 57	4%	- 22%
		step	stop strobe	58	- 59	23%	- 23%
		proportional	sequenced pulse effect, slow closing, fast opening (variable speed pulsing, from slow to fast)	60	- 108	24%	- 42%
		step	stop strobe	109	- 110	43%	- 43%
		proportional	sequenced pulse effect, fast closing, slow opening (variable speed pulsing, from slow to fast)	111	- 159	44%	- 62%
		step	stop strobe	160	- 161	63%	- 63%
		proportional	random strobe effect with variable speed from slow to fast	162	- 207	64%	- 81%
		step	stop strobe	208	- 209	82%	- 82%
		proportional	random strobe effect with variable speed and color temperature from slow to fast	210	- 255	82%	- 100%
Fixture: ParLite Led VariWhite 2700-6500°K			Table name: DMX 512 function				
Table number: 317		Edition: 1	Date: 23/03/2014				