

ProWash 250 LX



SPECIFICATIONS

- CMY color mixing
- 6 colors + open on
- CTO filter
- Beamshaper 180°
- Proportional zoom 6.5° - 31°
- Dimmer
- Mechanical strobe, synchronized, random, pulse effect
- Pan 530°, Tilt 284°, 16 bit

PHYSICAL SIZE

- Length: 350 mm (13.8 in)
- Width: 377 mm (14.8 in)
- Height: 535 mm (21.1 in), head straight up
- Weight: 23.5 kg (51.0 lbs)

LAMP AND BALLAST

- Type: Philips MSD 250W/2
- Color temperature: 8500 Kelvin
- Color rendering index: 70
- Average lamp life: 2000 hours
- Socket: GY 9.5
- Electromagnetic ballast

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990
- DMX channels:16
- Setting and addressing: LEDs display or remotely

ELECTRICAL SPECIFICATIONS/ CONNECTIONS

- AC power: 115/208/230/240 V, 50/60 Hz, 2 m (6.6 ft) integral cable without power plug
- Power consumption: 2 A at 230 V, 4.2 A at 115 V
- DMX data in/out: 3 pin locking XLR

ACCESSORIES

- Camlock plate (# 9111)

ProWash 250 LX
9097/L