
# TechnicalBrochure



## **AvantgardeSeries**



LED Luminaires and Retrofit Bulbs Licensing Program

SrL

Member Coemar Lighting



### **RigaLed Power**



**RGB** color mixing

Standard elliptical lens 13°x 40°

Silver die-cast aluminium body

Orientable yokes

IP20 weatherproof rating

**PHYSICAL SIZE** 

Length RigaLed Power 18: 500 mm (19.7 in) Length RigaLed Power 36: 1000 mm (39.4 in)

Width: 40 mm (1.6 in)

Height: 73 mm (2.9 in)

Weight RigaLed Power 18: 0.9 Kg (1.9 lbs) Weight RigaLed Power 36: 1.7 Kg (3.7 lbs)

**LIGHT SOURCE** 

RigaLed Power 18: 18 LEDs Cree, 6 Red, 6 Green, 6 Blue

RigaLed Power 36: 36 LEDs Cree, 12 Red, 12 Green, 12 Blue

**CONTROL PROTOCOL AND PROGRAMMING** With RegoBox or Concept Design

**ELECTRONICAL SPECIFICATIONS/CONNECTIONS** 

DC constant current power supply: 350 mA

Power consumption RigaLed Power 18: 21.6 W Power consumption RigaLed Power 36: 43.2 W **RJ45** connector

#### **ACCESSORIES**


12° lens kit


30° lens kit

50° lens kit


Ь.


45 mm [1.76"]







#### RigaLed Power 36 - Drawing Size









#### **RigaLed Power 36 - Photometrics Data**



#### RigaLed Power 36 - Photometrics Data

Rigaled Power 36											
distanza distance (mt)	1	2	3	4	5	6	7	8	9	10	
Red	1041	450	240	150	99	69	50	38	31	26	Resa Luminosa Light output (lux)
Green	1570	682	350	215	147	102	76	58	47	38	
Blue	294	135	69	41	28	19	14	10	8	7	
											-







**Coemar Lighting Srl** Via Carpenedolo, 90 46043, Castiglione delle Stiviere Mantova - Italy ph. +39 0376 1514412 fax. +39 0376 1514380

info@coemar.com www.coemar.com