



# Relite LED Kit +

Last update:  
29/03/2023



## ReLite LED Kit +

### Introducing

● Designed with + electronic and a new OLED display, this Retrofit lamp is the evolution of Tungsten, Daylight and VariWhite.

The + electronic with advanced LED controller enables a smooth dimming and it offers a higher luminous efficiency, with a color rendering index of the white range greater than 95.

### Configuration

● ReLite LED Kit + is available in three different versions

1. ReLite LED Kit S
2. ReLite LED Kit M
3. ReLite LED Kit L

### Key Features

- LED retrofit lamp
- Tungsten or Daylight COB LED
- VariWhite LEDs module
- CRI 90 or CRI > 95 (T and D version)
- CRI ≥ 95 up to 97 (VariWhite version)
- CCT Fixed white 3.200 K or 5.600 K (T/D version)
- CCT proportional control 2.700 K → 6.500 K (VariWhite version)
- Linear dimming from 0% to 100% via DMX
- DMX-512, RDM (Remote Device Management), Wireless (optional by LumenRadio)
- Thermal protection
- Guaranteed flicker free
- Customizable retrofit for each product
- European Conformity certification

## General

|                                       |  |
|---------------------------------------|--|
| ● LED Source                          | Tungsten or Daylight COB LED<br>VariWhite LEDs module  |
| ● CCT Range                           | ● ● ● ● ● ● Fixed white 3.200 K or 5.600 K (T/D version)<br>● ● ● ● ● ● Proportional control 2.700 K → 6.500 K (VariWhite version) |
| ● Color Rendition Average             | CRI>90 or CRI> 95 (T/D version)<br>CRI ≥ 95 up to 97 (VariWhite version)   |
| ● Dimming                             | Smooth 100% to 0%, 5 Selectable Curves - Exponential, Logarithmic, Linear, Halo and Standard                                       |
| ● Dimming Smooth Selection            | Fast, Slow and Very Slow   |
| ● Camera flicker control/Hz range     | Yes, 600 to 20.000 Hz (20.000 Hz on HD version)  |
| ● Calibrated Cob                      | Yes  |
| ● L80 Rating<br>(hours to 80% output) | 50.000 Hours   |
| ● Compatibility                       | Fast retrofitting on products like Arri, De Sisti, ADB and more  |

## Electrical

|                     |  |
|---------------------|--|
| ● Voltage Input     | 80-264 V, 50/60 Hz, auto-sensing   |
| ● Power Consumption | 90-350 W depending on the LED module and the size / model of the fixture |
| ● Power Connection  | In and Out PowerCON TRUE1 Top connectors                                 |
| ● Data Connection   | In and Out DMX 5 pin locking XLR connectors                              |

## Thermal

|                                 |  |
|---------------------------------|--|
| ● Thermal protection            | Yes  |
| ● Ambient Operating Temperature | 0°C - +40°C (32°F - 104°F)                                     |
| ● Cooling                       | Yes, 4 different settings: Silent, Studio, Auto, DMX regulated |

## Control

|                     |  |
|---------------------|--|
| ● Protocols         | DMX-512, RDM (Remote Device Management), Wireless (optional by LumenRadio) |
| ● RDM configuration | Yes  |
| ● DMX Channels      | 5 / 1 (T/D version)<br>5 / 2 / 1 (VariWhite version)                       |
| ● Display           | Graphic OLED   |
| ● Software upload   | Through DMX input (with RDM interface code AC10011A001)                    |

## Physical

|                    |  |
|--------------------|--|
| ● Mounting Options | With clamp or customized fixing system for installation on the fixture |
| ● Materials        | Alluminium and technopolymer   |
| ● IP Rating        | IP20   |
| ● Color options    | Black (standard)   |

**5 Channels**

01 → Master Dimmer

02 → Dimmer Fine

03 → White Tone

04 → Strobe Effect

05 → Special Functions

**2 Channels**

01 → Master Dimmer

02 → White Tone

**1 Channel**

01 → Master Dimer

**5 Channels**

01 → Master Dimmer

02 → Spare Channel

03 → Dimmer Fine

04 → Strobe Effect


05 → Special Functions

**1 Channels**

01 → Master Dimmer


Drawing Size

ReLite LED Kit M/L



| Lenght  | Width   | Height  | Weight  |
|---------|---------|---------|---------|
| 210 mm  | 124 mm  | 90 mm   | 2.5 Kg  |
| 8.26 in | 4.88 in | 3.54 in | 5.5 lbs |

ReLite LED Kit S




| Lenght  | Width   | Height  | Weight   |
|---------|---------|---------|----------|
| 190 mm  | 110 mm  | 73 mm   | 1.5 Kg   |
| 7.48 in | 4.33 in | 2.87 in | 3.31 lbs |



Broadcast - MDR Landesfunkhaus , Magdeburg, Germany

|         |  |
|---------|--|
| Product | ReLite Kit VW for DeSisti Leonardo 2KW |
| CCT     | 2.700 → 6.500 K                        |
| CRI     | 95 up to 97                            |
| Control | DMX                                    |
| Dealer  | Vision Two GmbH                        |





Theatre - Salzburg Festspiele Theater, Salzburg, Austria

|         |                     |
|---------|---------------------|
| Product | ReLite Kit T        |
| CCT     | 3.200 K             |
| CRI     | 90                  |
| Control | DMX                 |
| Dealer  | LB-electronics GmbH |





Events - Neumann & Müller warehouse, Germany

|          |                  |
|----------|------------------|
| Product  | ReLite Kit VW    |
| CCT      | 2.700 → 6.500 K  |
| CRI      | 90               |
| Customer | Neumann & Müller |
| Dealer   | Vision Two GmbH  |



● Coemar Lighting S.r.l.

Via Carpenedolo, 90  
46043, Castiglione delle Stiviere (MN) – Italy

P. +39 0376 1514412

M1. info@coemar.com

M2. service@coemar.com

W. coemar.com

P.iva – C.f. 02415330204

