

LEDko EXT M VariWhite
DMX chart (5 channels)

channel	function	type of control	effect	decimal		percentage	
1	master dimmer	proportional	adjust luminous output intensity from 0 to 100%	0	- 255	0%	- 100%
2	dimmer fine	proportional	fine dimmer control 16 bit	0	- 255	0%	- 100%
3	white tone	step	2.800 K	0	- 10	0%	- 4%
		proportional	proportional value from 2.800 K to 3.200 K	11	- 33	4%	- 13%
		step	3.200 K	34	- 60	13%	- 24%
		proportional	proportional value from 3.200 K to 4.000 K	61	- 87	24%	- 34%
		step	4.000 K	88	- 114	35%	- 45%
		proportional	proportional value from 4.000 K to 5.000 K	115	- 141	45%	- 55%
		step	5.000 K	142	- 168	56%	- 66%
		proportional	proportional value from 5.000 K to 5.600 K	169	- 195	66%	- 76%
		step	5.600 K	196	- 222	77%	- 87%
		proportional	proportional value from 5.600 K to 6.000 K	223	- 238	87%	- 93%
		step	6.000 K	239	- 255	94%	- 100%
4	strobe	step	no effect	0	- 9	0%	- 4%
		proportional	variable speed strobing effect, from slow to fast	10	- 57	4%	- 22%
		step	stop strobe	58	- 59	23%	- 23%
		proportional	sequenced pulse effect, slow closing, fast opening (variable speed pulsing, from slow to fast)	60	- 108	24%	- 42%
		step	stop strobe	109	- 110	43%	- 43%
		proportional	sequenced pulse effect, fast closing, slow opening (variable speed pulsing, from slow to fast)	111	- 159	44%	- 62%
		step	stop strobe	160	- 161	63%	- 63%
		proportional	random strobe effect with variable speed from slow to fast	162	- 207	64%	- 81%
		step	stop strobe	208	- 209	82%	- 82%
		proportional	random strobe effect with variable speed from slow to fast	210	- 255	82%	- 100%
5	special functions	step	park	0	- 9	0%	- 4%
			600 Hz	10	- 22	4%	- 9%
			no effect	23	- 199	9%	- 78%
			LED control frequency tuning 1.500 Hz	200	- 205	78%	- 80%
			LED control frequency tuning 2.000 Hz	206	- 211	81%	- 83%
			LED control frequency tuning 5.000 Hz	212	- 217	83%	- 85%
		proportional	no effect	218	- 240	85%	94%
		step	LED control frequency tuning 20.000 Hz	241	- 255	95%	- 100%
Projector: LEDko EXT M VariWhite			Chart name: DMX512 function		software version: 0.052		
Edition: 1.2			Date: 12.01.2023				

LEDko EXT M VariWhite
 DMX chart (2/1 channels)

channel		function	type of control	effect	decimal		percentage	
2	1							
1	1	master dimmer	proportional	adjust luminous output intensity from 0 to 100%	0	- 255	0%	- 100%
2	-	white tone	proportional	proportional value from 2.800 K to 6.000 K	0	- 255	0%	- 100%
Projector: LEDko EXT M VariWhite				Chart name: DMX512 function	software version: 0.052			
Edition: 1.2				Date: 12.01.2023				

LEDko EXT M VariWhite
DMX chart (Sunrise mode)

channel	function	type of control	effect	decimal		percentage	
1	master dimmer	proportional	adjust luminous output intensity from 0 to 100%	0	- 255	0%	- 100%
2	dimmer fine	proportional	fine dimmer control 16 bit	0	- 255	0%	- 100%
3	proportional cct	proportional	2.800 K	0	- 7	0%	- 3%
			proportional value from 2.800 K to 4000 K	8	- 86	3%	- 34%
			4.000 K	87		34%	
			proportional value from 4.000 to 5.000 K	88	- 152	35%	- 60%
			5.000 K	153		60%	
			proportional value from 5.000 to 5.600 K	154	- 192	60%	- 75%
			5.600 K	193		76%	
			proportional value from 5.600 K to 6.000 K	194	- 224	76%	- 88%
			6.000 K	225	- 255	88%	- 100%
4	step cct	step	no effect	0	- 9	0%	- 4%
			2.800 K	10	- 50	4%	- 20%
			3.200 K	51	- 91	20%	- 36%
			4.000 K	92	- 132	36%	- 52%
			5.000 K	133	- 173	52%	- 68%
			5.600 K	174	- 213	68%	- 84%
			6.000 K	214	- 255	84%	- 100%
5	special functions	step	park	0	- 9	0%	- 4%
			600 Hz	10	- 22	4%	- 9%
			no effect	23	- 199	9%	- 78%
			LED control frequency tuning 1.500 Hz	200	- 205	78%	- 80%
			LED control frequency tuning 2.000 Hz	206	- 211	81%	- 83%
			LED control frequency tuning 5.000 Hz	212	- 217	83%	- 85%
			no effect	218	- 240	85%	- 94%
			LED control frequency tuning 20.000 Hz	241	- 255	95%	- 100%
Note 1: If channels 3 and 4 are used simultaneously, channel 4 prevails.							
Projector: LEDko EXT M VariWhite		Chart name: DMX512 function		software version: 0.052			
Edition: 1.2		Date: 12.01.2023					

