

SunLite LED VariWhite

PHOTOMETRICAL DATA

NARROW BEAM: 1/2 Peak Angle 21°

Distance (m)	3	6	9	12	15	18	21	24	27	30
Luminous Emittance (lux)										
2.700 K	3198	800	355	200	128	89	65	50	39	32
6.500 K	11440	2860	1271	715	458	318	233	179	141	114
FULL	14355	3589	1595	897	574	399	293	224	177	144
1/2 Peak Angle Diameter Ø (m)	1.11	2.22	3.34	4.45	5.56	6.67	7.78	8.90	10.01	11.12

MEDIUM BEAM: 1/2 Peak Angle 25°

Distance (m)	3	6	9	12	15	18	21	24	27	30
Luminous Emittance (lux)										
2.700 K	2035	509	226	127	81	57	42	32	25	20
6.500 K	7364	1841	818	460	295	205	150	115	91	74
FULL	9283	2321	1031	580	371	258	189	145	115	93
1/2 Peak Angle Diameter Ø (m)	1.33	2.66	3.99	5.32	6.65	7.98	9.31	10.64	11.97	13.30

WIDE BEAM: 1/2 Peak Angle 34°

Distance (m)	1	2	3	4	5	6	7	8	9	10
Luminous Emittance (lux)										
2.700 K	11322	2831	1258	708	453	315	231	177	140	113
6.500 K	42228	10557	4692	2639	1689	1173	862	660	521	422
FULL	52722	13181	5858	3295	2109	1465	1076	824	651	527
1/2 Peak Angle Diameter Ø (m)	0.61	1.22	1.83	2.45	3.06	3.67	4.28	4.89	5.50	6.11

ULTRA WIDE BEAM: 1/2 Peak Angle 54°

Distance (m)	1	2	3	4	5	6	7	8	9	10
Luminous Emittance (lux)										
2.700 K	4608	1152	512	288	184	128	94	72	57	46
6.500 K	16983	4246	1887	1061	679	472	347	265	210	170
FULL	21537	5384	2393	1346	861	598	440	337	266	215
1/2 Peak Angle Diameter Ø (m)	1.02	2.04	3.06	4.08	5.10	6.11	7.13	8.15	9.17	10.19